



Rodamiento de bolas 2308-E-2RS1-TN9-SKF

2308-E-2RS1-TN9-SKF



Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designations	
d	D	B	C	C ₉₀	P ₀	Reference speed	Limiting speed	kg	Bearing with cylindrical bore	tapered bore
mm						min	min			
40	90	23	14	14	0,82	34 000	10 000	0,93	2308 ETN9	2308 ETN9

Dimensions				Abutment and fillet dimensions			Calculation factors			
d	d ₂	D ₁	r _{1,2} mm	r _a mm	r _b mm	r _c mm	k _r	e	Y ₁	Y ₂
mm										
40	53,7	79,2	1,5	49	81	1,5	0,05	0,4	1,6	2,4



Rodamiento de bolas 2308-E-2RS1-TN9-SKF

Caractéristique	Valeur
d - Diámetro interior (mm)	40
D - Diámetro exterior (mm)	90
C - Espesor (mm)	33
Marca	SKF
Tipo del rodamiento	De bolas
Juego	Estándar
Tipo de sellado	Doble estanco plástico (2RS, 2RS1, DDU, LLU, EE)
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	2300
Unidad de venta	pieza

