



Rodamiento de bolas a rótula 1200-TVH-C3-FAG

1200-TVH-C3-FAG


**LE BON
ROULEMENT**


d	10 mm
D	30 mm
B	9 mm
D _h	23.3 mm
D _{h max}	25.8 mm
d _i	16.3 mm
d _{i min}	14.2 mm
r _{h max}	0.6 mm
r _{h min}	0.6 mm
m	0.034 kg masse
C _r	5700 N charge dyn. de base, radiale
C _{0r}	1180 N charge statique de base, radiale
e	0.32
Y ₁	1.95
Y ₂	3.02
Y ₀	2.05
n ₀	28500 1/min vitesse limite
n _B	22100 1/min vitesse de base
C _{0r}	73 N charge limite radiale à la fatigue



Rodamiento de bolas a rótula 1200-TVH-C3-FAG

Caractéristique	Valeur
d - Diámetro interior (mm)	10
D - Diámetro exterior (mm)	30
C - Espesor (mm)	9
Marca	FAG
Tipo del rodamiento	De bolas
Juego	Alta velocidad (C3, J30)
Tipo de sellado	No estanco
Tipo de jaula	Poliamido
Agujero	Cilíndrico/a
Rodamiento serie	1200
Unidad de venta	pieza

