

Rodamiento de bolas 6840

6840





| Dimensions (mm)<br>Dimension (mm) |           |           | Coefficient de charge (N)<br>Load rating (kN) |                            | Vitesse limite (tr/min)<br>Speed limit (rpm) |              | Poids (kg)<br>Weight (lb) | Sigle<br>Designation |
|-----------------------------------|-----------|-----------|-----------------------------------------------|----------------------------|----------------------------------------------|--------------|---------------------------|----------------------|
| d<br>(mm)                         | D<br>(mm) | B<br>(mm) | Dynamique<br>C                                | Statique<br>C <sub>0</sub> | Lubrification<br>Lubrication                 |              |                           |                      |
|                                   |           |           |                                               |                            | Graisse<br>Grease                            | Huile<br>Oil |                           |                      |
| 200                               | 210       | 26        | 75.6                                          | 100                        | 3400                                         | 2800         | 2.7                       | 6840                 |



**Rodamiento de bolas 6840**

| Caractéristique            | Valeur                |
|----------------------------|-----------------------|
| d - Diámetro interior (mm) | 200                   |
| D - Diámetro exterior (mm) | 250                   |
| C - Espesor (mm)           | 24                    |
| Marca                      | Genérica alta calidad |
| Tipo del rodamiento        | De bolas              |
| Juego                      | Estándar              |
| Tipo de sellado            | No estanco            |
| Tipo de jaula              | Acero                 |
| Rodamiento serie           | 61800 - 6800          |
| Unidad de venta            | pieza                 |

